


Service Manual Plate Compactor

(PC 30) S/N 769500101 & Above

(PC 60) S/N 608500101 & Above

(PC 62) S/N 608600101 & Above





Bobcat Company 2011

MAINTENANCE SAFETY




Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.

W-2003-0807

A

Safety Alert Symbol: This symbol with a warning statement, means: "Warning, be alert! Your safety is involved!" Carefully read the message that follows.



- ♠ Never service attachments / implements without instructions. See Operation & Maintenance Manual and Attachment / Implement Service Manual.
- Cleaning and maintenance are required daily.
- A Never service or adjust attachment / implement with the engine running unless instructed to do so in manual.
- Always lower the attachment / implement to the ground before lubricating or servicing.
- Avoid contact with leaking hydraulic fluid or diesel fuel under pressure. It can penetrate skin or eyes.
- Stop, cool and clean engine of flammable materials before checking fluids.
- ▲ Keep body, loose objects and clothing away from moving parts, electrical contacts, hot parts and exhaust.
- Safety glasses are needed for eye protection from electrical arcs, battery acid, compressed springs, fluids under pressure and flying debris or when tools are used. Use eye protection approved for type of welding.

MSW30-0409

Thanks very much for your reading,

Want to get more information,

Please click here, Then get the complete
manual



NOTE:

If there is no response to click on the link above, please download the PDF document first, and then click on it.

Have any questions please write to me: admin@servicemanualperfect.com



CONTENTS

SAFETY AND MAINTENANCE	10-01
HYDRAULIC SYSTEM	
MAINFRAME	30-01
SPECIFICATIONS	SPEC-01
ALDHARETICAL INDEX	INDEX 01



1-4

FOREWORD


SERIAL NUMBER LOCATION		
DELIVERY REPORT	1-7	
ATTACHMENT IDENTIFICATION	1-8	



SERIAL NUMBER LOCATION

Attachment Serial Number


Figure 1



Always use the serial number of the Bobcat plate compactor when requesting service information or when ordering parts. Early or later models (identification made by serial number) may use different parts, or it may be necessary to use a different procedure in doing a specific service operation [Figure 1].


DELIVERY REPORT


Figure 2




The delivery report [Figure 2] must be completed by the dealer and signed by the owner or operator when the Bobcat plate compactor is delivered. An explanation of the form must be given to the owner.


ATTACHMENT IDENTIFICATION







ATTACHMENT IDENTIFICATION (CONT'D)



SAFETY AND MAINTENANCE

TROUBLESHOOTING	
SERVICE SCHEDULE	
DAILY INSPECTION	10-30-1 10-30-1
LUBRICATION	10-40-1



TROUBLESHOOTING

Chart



Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.

W-2003-0903

If the attachment is not working correctly, check the hydraulic system of the machine thoroughly before making any repairs on the attachment. Attachment problems can be affected by a hydraulic system that is not operating to specifications. Connect a flow meter to the machine to check the hydraulic pump output, relief valve setting and tube lines to check flow and pressure. (See the machine's Service Manual for the correct procedure to connect the flow meter.)

Use the following troubleshooting chart to locate and correct problems which most often occur with the attachment.

PROBLEM	CAUSE	CORRECTION	
Compactor does not operate.	No hydraulic flow to the compactor.	Check the hydraulic flow to the compactor.	
	Damaged quick couplers or hoses.	Replace quick couplers or hoses.	
	Machine fluid reservoir is low.	Add hydraulic fluid to the reservoir on the excavator. Replace bearings. Adjust main relief valve to correct setting. Check flow of hydraulic pump. Repair or replace as needed.	
	Compactor bearings seized.		
	Excavator main relief valve set too low.		
	Excavator hydraulic pump not working.		
	Hydraulic flow to compactor in wrong direction (check valve in system).	Change flow direction with auxiliary hydraulic pedal.	
Rapid bearing failure.	Lack of lubrication	Lubricate both bearings every 40 hours.	
Rapid shock mount failure.	Excessive down pressure.	Stretch shock mounts no more than 51 - 64 mm (2.0 - 2,500 in) during operation.	
	Cold weather operation.	Warm up according to WARM UP procedure. See Operation and Maintenance Manual.	
Failure to achieve required compaction specifications.	Incorrect use.	See OPERATION section of the Operation and Maintenance Manual.	
	Moisture / soil content incorrect for specified density.	Correct condition of soil or compactor specifications are not reasonable for conditions.	



16 of 80

SERVICE SCHEDULE

Chart

Maintenance work must be done at regular interval. Failure to do so will result in excessive wear and early failures. The service schedule is a guide for correct maintenance of the Bobcat plate compactor.



Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.

W-2003-0903 W-2003-0903

SERVICE SCHEDULE		FREQUENCY	
ITEM	SERVICE REQUIRED	10 HOURS	40 HOURS
General Items	Check for loose or missing fasteners. Tighten or replace as needed.		
Shock Mounts	Check shock mounts for rips or tears. Rotate the shock mounts 180° if cracks occur at the top outer crease of the shock mount.		
Bearings	Lubricate the bearings with (2) pumps of grease.		

