




---

# Service Manual

## Tiller

---

**(40 Tiller) S/N APFW00101 & Above**  
**(62 Tiller) S/N 055200101 & Above**  
**(76 Tiller) S/N 055100101 & Above**



Dealer Copy -- Not for Resale





# MAINTENANCE SAFETY



## WARNING


Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.

W-2003-0807











**Safety Alert Symbol:** This symbol with a warning statement, means: "Warning, be alert! Your safety is involved!" Carefully read the message that follows.

CORRECT



P-90216

-  Never service attachments / implements without instructions. See Operation & Maintenance Manual and Attachment / Implement Service Manual.
-  Cleaning and maintenance are required daily.
-  Never service or adjust attachment / implement with the engine running unless instructed to do so in manual.
-  Always lower the attachment / implement to the ground before lubricating or servicing.
-  Avoid contact with leaking hydraulic fluid or diesel fuel under pressure. It can penetrate skin or eyes.
-  Stop, cool and clean engine of flammable materials before checking fluids.
-  Keep body, loose objects and clothing away from moving parts, electrical contacts, hot parts and exhaust.
-  Safety glasses are needed for eye protection from electrical arcs, battery acid, compressed springs, fluids under pressure and flying debris or when tools are used. Use eye protection approved for type of welding.

Dealer Copy -- Not for Resale

MSW30-0409

**Thanks very much for your reading,  
Want to get more information,  
Please click here, Then get the complete  
manual**

**JustClickHere** 

**NOTE:**

**If there is no response to click on the link above,  
please download the PDF document first, and then  
click on it.**

**Have any questions please write to me:  
[admin@servicemanualperfect.com](mailto:admin@servicemanualperfect.com)**



## CONTENTS

SAFETY AND MAINTENANCE .....	10-01
HYDRAULIC SYSTEM .....	20-01
MAINFRAME .....	30-01
SPECIFICATIONS .....	SPEC-01
ALPHABETICAL INDEX .....	INDEX-01

Dealer Copy -- Not for Resale



**Bobcat®**

**FOREWORD**

SERIAL NUMBER LOCATION ..... 1-7

Attachment Serial Number ..... 1-7

DELIVERY REPORT ..... 1-7

ATTACHMENT IDENTIFICATION ..... 1-8

40 Tiller ..... 1-8

62 Tiller And 76 Tiller ..... 1-9

Dealer Copy -- Not for Resale






**Bobcat®**

Dealer Copy -- Not for Resale

SERIAL NUMBER LOCATION

Attachment Serial Number

Figure 1



Always use the serial number [Figure 1] of the tiller when requesting service information or when ordering parts. Early or later models (identification made by serial number) may use different parts, or it may be necessary to use a different procedure in doing a specific service operation.

DELIVERY REPORT

Figure 2


A scanned image of the Bobcat Delivery Report form. The form is titled 'Bobcat Delivery Report Attachments' and includes fields for Dealer Name, Dealer Address, Dealer Phone, and Dealer Fax. It also has a section for 'WARNING' with a list of items to be inspected, such as 'Check for proper operation of all controls', 'Check for proper operation of all safety devices', and 'Check for proper operation of all hydraulic systems'. The form is signed by the Dealer Representative and the Operator. A label 'NA7494' is in the bottom right corner.

The delivery report [Figure 2] must be completed by the dealer and signed by the owner or operator when the Bobcat tiller is delivered. An explanation of the form must be given to the owner.

Dealer Copy -- Not for Resale

ATTACHMENT IDENTIFICATION


40 Tiller



Dealer Copy -- Not for Resale

ATTACHMENT IDENTIFICATION (CONT'D)

62 Tiller And 76 Tiller



Dealer Copy -- Not for Resale

P105011



**Bobcat®**

Dealer Copy -- Not for Resale

**SAFETY AND MAINTENANCE**

TROUBLESHOOTING ..... 10-10-1
    Chart ..... 10-10-1

DAILY INSPECTION ..... 10-20-1
    Attachment Mounting Frame ..... 10-20-1
    Bob-Tach™ ..... 10-20-1

Dealer Copy -- Not for Resale




**Bobcat®**

Dealer Copy -- Not for Resale

## TROUBLESHOOTING

### Chart

 <b>WARNING</b>	<p>Instructions are necessary before operating or servicing machine. Read and understand the Operation &amp; Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.</p> <p style="text-align: right;">W-2003-0807</p>
--	--

If the attachment is not working correctly, check the hydraulic system of the machine thoroughly before making any repairs on the attachment. Attachment problems can be affected by a hydraulic system that is not operating to specifications. Connect a flow meter to the machine to check the hydraulic pump output, relief valve setting and tube lines to check flow and pressure. (See the machine's Service Manual for the correct procedure to connect the flow meter.)

Use the following troubleshooting chart to locate and correct problems which most often occur with the attachment.

PROBLEM	CAUSE	CORRECTION
Tiller will not function.	Hydraulics hoses improperly connected.	Check the hydraulic quick couplers to make sure they are connected properly.
	Auxiliary hydraulics not engaged.	Engage auxiliary hydraulics. (See the machine's Operation & Maintenance Manual and Operator's Handbook for correct procedure.)
Tiller leaves an uneven finish (half smooth, half rough).	Tiller tines are either missing, or are worn.	Replace broken tines. Be sure all tines are present.
Tiller leaves a rough finish.	Tiller is being operated at low rpm's.	Increase machine rpm's.
	Tiller tines are either missing, or are worn.	Replace broken tines. Be sure all tines are present.
	Tiller is traveling too fast.	Decrease the rate of travel.
Tiller operation causes the machine to vibrate roughly.	Tiller is operating in the wrong direction.	Check to make sure tiller shaft is rotating in the opposite direction of travel.
	Tiller is traveling too fast.	Decrease the rate of travel.
	Machine arms / boom not positioned in cradle.	Lower machine arms / boom fully.

Dealer Copy -- Not for Resale





**Bobcat®**

Dealer Copy -- Not for Resale

## DAILY INSPECTION

### Attachment Mounting Frame

Figure 10-20-1





Figure 10-20-2



Inspect the Bob-Tach™ wedge mounts (Item 1), mounting flange (Item 2) [Figure 10-20-1] or [Figure 10-20-2] and all welds on the tiller for wear and damage each time the tiller is removed from the machine.

Inspect the Bob-Tach centering guide (Item 3) [Figure 10-20-1] (40 tiller only) for damage.

Frequently inspect the tiller to ensure that all components are secure and that all bolts and nuts are thoroughly tightened.

## Bob-Tach™

### Hand Lever Bob-Tach


# ! WARNING

## AVOID INJURY OR DEATH

The Bob-Tach wedges must extend through the holes in the attachment mounting frame. Levers must be fully down and locked. Failure to secure wedges can allow attachment to come off.

W-2715-0208

Figure 10-20-3



Push down on the Bob-Tach levers until they are fully engaged in the locked position [Figure 10-20-3] (wedges fully extended through the attachment mounting frame holes).

The levers and wedges must move freely [Figure 10-20-3].


Dealer Copy -- Not for Resale

## DAILY INSPECTION (CONT'D)

### Bob-Tach (Cont'd)

#### Hand Lever Bob-Tach (Cont'd)

Figure 10-20-4



The wedges must extend through the holes in the attachment mounting frame, securely fastening the attachment to the Bob-Tach [Figure 10-20-4].

**NOTE:** If the wedge does not contact the lower edge of the hole, the attachment will be loose and can come off the Bob-Tach.

Inspect the mounting frame on the attachment. (See the machine's Operation & Maintenance Manual for inspecting the Bob-Tach). Replace any parts that are damaged, bent or missing. Keep all fasteners tight. Look for cracked welds. Contact your Bobcat dealer for repair or replacement parts.

Lubricate the wedges. (See the machine's Operation & Maintenance Manual for the correct procedure.)