
337 341



Service Manual

337 - S/N 234611001 & Above 341 - S/N 234711001 & Above (G Series)




Printed in U.S.A.

MAINTENANCE SAFETY

WARNING


Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death. W-2003-0807

Safety Alert Symbol: This symbol with a warning statement, means: "Warning, be alert! Your safety is involved!" Carefully read the message that follows.







Use the correct procedure to lift and support the excavator.



 Vent exhaust to outside when engine must be run for service.
Exhaust system must be tightly sealed. Exhaust fumes can kill without warning.



- Keep body, jewelry and clothing away from moving parts, electrical contact, hot parts and exhaust.
- Wear eye protection to guard from battery acid, compressed springs, fluids under pressure and flying debris when engines are running or tools are used. Use eye protections approved for type of welding.
- Keep tailgate closed except for service. Close and latch tailgate before operating the excavator.



Maintenance procedures which are given in the Operation & Maintenance Manual can be performed by the owner/ operator without any specific technical training. Maintenance procedures which are **not** in the Operation & Maintenance Manual must be performed **ONLY BY QUALIFIED BOBCAT SERVICE PERSONNEL.** Always use genuine Bobcat **replacement parts.** The Service Safety Training Course is available from your Bobcat dealer.



AIR CLEANER	10-01, 60-01
AIR CONDITIONING SERVICE	70-01
AIR CONDITIONING SYSTEM FLOW	
ALTERNATOR	50-01
ARM	40-01
ARM CYLINDER	20-01

BASIC TROUBLESHOOTING BATTERY	
BLADE	30-01
BLADE CONTROL	40-01
BLADE CYLINDER	
BOOM	40-01
BOOM CYLINDER	20-01
BOOM SWING CYLINDER	20-01
BOOM SWING LOCK VALVE	20-01
BUCKET	40-01
BUCKET CYLINDER	20-01
BUILD UP VALVE	20-01

CAB	40-01
CASE DRAIN FILTER MOUNT	20-01
CLAMP	40-01
CLAMP CYLINDER	20-01
COMPONENTS	70-01
COMPRESSOR	70-01
CONDENSOR	70-01
CONTROL LINKAGE ASSEMBLY	40-01
CONTROL PATTERN SELECTOR VALVE	20-01
CONVERSIONS	SPEC-01
COOLING SYSTEM	10-01
CROSSPORT RELIEF VALVE	20-01

DELUXE INSTRUMENT PANEL SETUP	50-01
DIAGNOSTICS SERVICE CODE	50-01
DIRECT TO TANK VALVE	20-01
DUAL SEQUENCE VALVE	20-01

ELECTRICAL SYSTEM INFORMATION ENGINE	
ENGINE ACCESSORY DRIVE BELT	10-01
ENGINE COMPONENTS AND TESTING	60-01
ENGINE FLYWHEEL	60-01
ENGINE LUBRICATION SYSTEM	10-01
ENGINE SPECIFICATIONS	SPEC-01
ENGINE SPEED CONTROL	40-01
EVAPORATOR	

EVAPORATOR/HEATER UNIT	70-01
EXPANSION VALVE	
FLOORMAT AND FLOOR PLATE	
FUEL, COOLANT AND LUBRICANTS	
FUEL LEVEL SENDER	50-01
FUEL SYSTEM	
FUEL TANK	40-01
GENERAL AIR CONDITIONING SERVICE	
GUIDELINES	70-01
	70.04
HEATER AIR FILTER	
HEATER COIL	
HEATER VALVE	
HYDRAULIC CONNECTION SPECIFICATIONS	
HYDRAULIC CONTROL VALVE	
HYDRAULIC FILTER MOUNT	
HYDRAULIC FLUID SPECIFICATIONS	
	20-01
HYDRAULIC PUMP START UP	
HYDRAULIC RESERVOIR	
HYDRAULIC SYSTEM	
HYDRAULIC SYSTEM INFORMATION	
HYDRAULIC X-CHANGE VALVE	20-01
LEFT CONSOLE	40.01
LEFT CONSOLE	
LIFTING AND BLOCKING THE EXCAVATOR	
LIFTING THE EXCAVATOR	
LIGHTS	
LUBRICATION OF THE EXCAVATOR	10-01
LOBRICATION OF THE EXCAVATOR	10-01
MAIN RELIEF VALVE	20-01
MANIFOLD ASSEMBLY/ACCUMULATOR	
MUFFLER	
OIL COOLER	20-01
OPERATOR CAB	
PORT RELIEF VALVES	20-01
PRESSURE REDUCING VALVE	
PRESSURE RELIEF VALVE	
PRESSURE SWITCH	70-01

Continued On Next Page

ALPHABETICAL INDEX (CONT'D)

RADIATOR	60-01
RECEIVER/DRYER	70-01
RECONDITIONING THE ENGINE	60-01
REGULAR MAINTENANCE	70-01
REMOVING AIR FROM HYDRAULIC SYSTEM	20-01
RIGHT CONSOLE	40-01
RIGHT CONTROL LEVER (JOYSTICK)	20-01
RIGHT PEDAL AND LINKAGE	40-01
RIGHT SIDE COVER	10-01
ROPS CANOPY	40-01

SAFETY	70-01
SEAT AND SEAT MOUNT	40-01
SEAT BELT	10-01
SERVICE SCHEDULE	10-01
SPARK ARRESTOR MUFFLER	10-01
SPECIFICATIONS	SPEC-01
STARTER	50-01
SWING CIRCLE GEAR	
SWING FRAME	40-01
SWING MOTOR	20-01
SWING MOTOR DRIVE CARRIER	20-01
SWIVEL JOINT	20-01
SYSTEM CHARGING AND RECLAMATION	70-01
SYSTEM TROUBLESHOOTING CHART	70-01

TAILGATE	10-01, 40-01
TEMPERATURE/PRESSURE	
THERMOSTAT	
TORQUE SPECIFICATIONS	SPEC-01
TRACK DAMAGE IDENTIFICATION	
TRACK FRAME	
TRACK IDLER	
TRACK ROLLER	
TRACKS	
TRANSPORTING THE EXCAVATOR	
TRAVEL CONTROLS	
TRAVEL CONTROL VALVE	20-01
TRAVEL MOTOR	10-01, 20-01
TROUBLESHOOTING	
TWO SPEED SWITCH	50-01
UPPERSTRUCTURE	40-01
X-CHANGE	40-01
X-CHANGE (HYDRAULIC)	

CONTENTS

FOREWORDIII
SAFETY INSTRUCTIONS V
FIRE PREVENTION
SERIAL NUMBER LOCATIONS
DELIVERY REPORT
BOBCAT EXCAVATOR IDENTIFICATION
SAFETY AND MAINTENANCE
HYDRAULIC SYSTEM
UNDERCARRIAGE
UPPERSTRUCTURE & SWING SECTION
ELECTRICAL SYSTEM AND ANALYSIS
ENGINE SERVICE
HEATING, VENTILATION, AIR CONDITIONING
SPECIFICATIONSSPEC-01

SAFETY AND MAINTENANCE

HYDRAULIC SYSTEM

UNDERCARRIAGE

UPPERSTRUCTURE & SWING SECTION

ELECTRICAL SYSTEM AND ANALYSIS

ENGINE SERVICE

HVAC

SPECIFICATIONS



FOREWORD

This manual is for the Bobcat excavator mechanic. It provides necessary servicing and adjustment procedures for the Bobcat excavator and its component parts and systems. Refer to the Operation & Maintenance Manual for operating instructions, starting procedure, daily checks, etc.

A general inspection of the following items must be made after the excavator has had service or repair:

condition.

supply.

12. Inspect for

10. Check for correct function of

11. Check hydraulic fluid level,

engine oil level and fuel

fuel.

oil


or

indicator lamps.

1. Check that the ROPS/TOPS/ FOPS is in good condition and is not modified.



2. Check that **ROPS/TOPS** mounting hardware is tightened and is Bobcat approved.




- 4. Machine signs (decals) must be legible and in the correct location.
- 5. Travel levers, control levers and foot pedals must return to neutral. Check that the pedal locks are in working order.
- 6. Check for correct function of the work lights.



WARNING

hydraulic fluid leaks.


- 14. Check the condition of the battery and cables.
- 15. Inspect the air cleaner for damage or leaks. Check the condition of the element.
- 16. Check the electrical charging system.


















FW EXC-0509 SM





7. Enclosure door latches must open and close freely.



8. Attachment locking pins must function correctly and be in good condition.



Ш



17. Check tracks for wear and tension. Use only approved tracks.



18. Inspect for loose or broken parts or connections.



19. Check for any field modification not completed.




20. Operate the machine and check all functions.



- 21. Check the control console interlocks for correct function.
- Inspect the X-Change[™] for wear or damage. Repair or replace damaged parts.
- 23. Check function or condition of all equipped options and accessories (examples: special applications kit, motion alarm, etc.).
- 24. Recommend to the owner that all necessary corrections be made before the machine is returned to service.









CALIFORNIA PROPOSITION 65 WARNING

Diesel engine exhaust and some of its constituents are known to the state of California to cause cancer, birth defects and other reproductive harm.

FW EXC-0509 SM

337/341 Excavator Service Manual



Safety Alert Symbol

This symbol with a warning statement means: "Warning, be alert! Your safety is involved!" Carefully read the message that follows.



Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Operator's Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.

W-2003-0903

IMPORTANT

This notice identifies procedures which must be followed to avoid damage to the machine.

I-2019-0284

DANGER

The signal word DANGER on the machine and in the manuals indicates a hazardous situation which, if not avoided, will result in death or serious injury.

D-1002-1107

The signal word WARNING on the machine and in the manuals indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

W-2044-1107

The following publications provide information on the safe use and maintenance of the Bobcat machine and attachments:

- The Delivery Report is used to assure that complete instructions have been given to the new owner and that the machine is in safe operating condition.
- The Operation & Maintenance Manual delivered with the machine or attachment contains operating information as well as routine maintenance and service procedures. It is a part of the machine and can be stored in a container provided on the machine. Replacement Operation & Maintenance Manuals can be ordered from your Bobcat dealer.
- Machine signs (decals) instruct on the safe operation and care of your Bobcat machine or attachment. The signs and their locations are shown in the Operation & Maintenance Manual. Replacement signs are available from your Bobcat dealer.
- An Operator's Handbook fastened to the operator cab. It's brief instructions are convenient to the operator. The handbook is available from your dealer in an English edition or one of many other languages. See your Bobcat dealer for more information on translated versions.
- The AEM Safety Manual delivered with the machine gives general safety information.
- The Service Manual and Parts Manual are available from your dealer for use by mechanics to do shop-type service and repair work.
- The Compact Excavator Operator Training Course is available through your local dealer or at www.training.bobcat.com or www.bobcat.com. This course is intended to provide rules and practices of correct operation of the Bobcat excavator. The course is available in English and Spanish versions.
- Service Safety Training Courses are available from your Bobcat dealer or at **www.training.bobcat.com** or **www.bobcat.com**. They provide information for safe and correct service procedures.
- The Bobcat compact excavator Safety Video is available from your Bobcat dealer or at www.training.bobcat.com or www.bobcat.com.

SAFETY INSTRUCTIONS (CONT'D)

The dealer and owner / operator review the recommended uses of the product when delivered. If the owner / operator will be using the machine for a different application(s) he or she must ask the dealer for recommendations on the new use.





Call Before You Dig Dial 811 (USA Only) 1-888-258-0808 (USA & Canada)

When you call, you will be directed to a location in your state / province, or city for information about buried lines (telephone, cable TV, water, sewer, gas, etc.).

Cutting or drilling concrete containing sand or rock containing quartz may result in exposure to silica dust. Do not exceed Permissible Exposure Limits (PEL) to silica dust as determined by OSHA or other job site Rules and Regulations. Use a respirator, water spray or other means to control dust. Silica dust can cause lung disease and is known to the state of California to cause cancer.

SI EXC-0308 SM



Maintenance

The machine and some attachments have components that are at high temperatures under normal operating conditions. The primary source of high temperatures is the engine and exhaust system. The electrical system, if damaged or incorrectly maintained, can be a source of arcs or sparks.

Flammable debris (leaves, straw, etc.) must be removed regularly. If flammable debris is allowed to accumulate, it can cause a fire hazard. Clean often to avoid this accumulation. Flammable debris in the engine compartment is a potential fire hazard.

The operator's area, engine compartment and engine cooling system must be inspected every day and cleaned if necessary to prevent fire hazards and overheating.

All fuels, most lubricants and some coolants mixtures are flammable. Flammable fluids that are leaking or spilled onto hot surfaces or onto electrical components can cause a fire.

Operation

Do not use the machine where exhaust, arcs, sparks or hot components can contact flammable material, explosive dust or gases.

Electrical



Check all electrical wiring and connections for damage. Keep the battery terminals clean and tight. Repair or replace any damaged part or wires that are loose or frayed.

Battery gas can explode and cause serious injury. Use the procedure in the Operation & Maintenance Manual for connecting the battery and for jump starting. Do not jump start or charge a frozen or damaged battery. Keep any open flames or sparks away from batteries. Do not smoke in battery charging area.

Hydraulic System

Check hydraulic tubes, hoses and fittings for damage and leakage. Never use open flame or bare skin to check for leaks. Hydraulic tubes and hoses must be properly routed and have adequate support and secure clamps. Tighten or replace any parts that show leakage.

Always clean fluid spills. Do not use gasoline or diesel fuel for cleaning parts. Use commercial nonflammable solvents.

Fueling



Stop the engine and let it cool before adding fuel. No smoking! Do not refuel a machine near open flames or sparks. Fill the fuel tank outdoors.

Starting

Do not use ether or starting fluids on any engine that has glow plugs. These starting aids can cause explosion and injure you or bystanders.

Use the procedure in the Operation & Maintenance Manual for connecting the battery and for jump starting.

Spark Arrestor Exhaust System

The spark arrestor exhaust system is designed to control the emission of hot particles from the engine and exhaust system, but the muffler and the exhaust gases are still hot.

Check the spark arrestor exhaust system regularly to make sure it is maintained and working properly. Use the procedure in the Operation & Maintenance Manual for cleaning the spark arrestor muffler (if equipped).

FIRE PREVENTION (CONT'D)

Welding And Grinding

Always clean the machine and attachment, disconnect the battery, and disconnect the wiring from the Bobcat controllers before welding. Cover rubber hoses, battery and all other flammable parts. Keep a fire extinguisher near the machine when welding.

Have good ventilation when grinding or welding painted parts. Wear dust mask when grinding painted parts. Toxic dust or gas can be produced.

Dust generated from repairing nonmetallic parts such as hoods, fenders or covers can be flammable or explosive. Repair such components in a well ventilated area away from open flames or sparks.

Fire Extinguishers



Know where fire extinguishers and first aid kits are located and how to use them. Inspect the fire extinguisher and service the fire extinguisher regularly. Obey the recommendations on the instructions plate.


SI EXC-0308 SM

SERIAL NUMBER LOCATIONS

Always use the serial number of the excavator when requesting service information or when ordering parts. Early or later models (identification made by serial number) may use different parts, or it may be necessary to use a different procedure in doing a specific service operation.

Excavator Serial Number

Figure 1



The excavator serial number plate (Item 1) [Figure 1] is located on the frame of the machine in the location shown.

Explanation of Excavator Serial Number:

XXXX XXXXX Module 2. - Production Sequence (Series) Module 1. - Model/ Engine Combination

- 1. The 4 digit Model/Engine Combination Module number identifies the model number and engine combination.
- 2. The 5 digit Production Sequence Number identifies the order which the excavator is produced.

Engine Serial Number

Figure 2






Figure 3




The engine serial number (Item 1) **[Figure 2]** & **[Figure 3]** is located on the engine in the location shown.

DELIVERY REPORT

Figure 4



The delivery report must be filled out by the dealer and signed by the owner or operator when the Bobcat Excavator is delivered. An explanation of the form must be given to the owner. Make sure it is filled out completely **[Figure 4]**.



Dear

Thanks very much for your visiting and patience.

Want to get more information,

Please click here, Go back to the page.

After your payment, you will have instant access to your download.

The Download Link will also be sent to your e-mail.

You will get the complete manual

Have any questions please write to me

admin@servicemanualperfect.com