

W14B LOADER

Table of Contents

DIVISION/SECTION	SECTION NO.	FORM NO.
1 GENERAL		
Safety Rules, Service Manual Introduction, and Torque Specifications	1001	8-42830
Fluids and Lubricants Chart, Maintenance Chart	1002	8-42830
General Engine Specifications	1010	8-27130
Detailed Engine Specifications	1024	8-26061
2 ENGINE		
Engine Removal and Installation, Radiator Removal and Installation	2000	8-42830
Engine Accessories (Air Cleaner, Ether Injection, Mufflers, Turbocharger)	2001	8-42830
Stall Tests	2002	8-24830
Cylinder Head and Valve Train	2415	8-26071
Cylinder Block, Crankshaft, Pistons, Rods, Camshaft, Oil Seals, Flywheel, and Crankshaft	2425	8-26081
Lubrication System	2445	8-26091
Cooling System	2455	8-26101
Turbocharger (Teardown)	2465	8-26110
Turbocharger Failure Analysis	2565	9-78235
3 FUEL SYSTEM		
Fuel lines, Fuel Tank, and Engine Controls	3001	8-42830
Fuel System and Filters	3410	8-26131
Bosch Fuel Injection Pump, Drive Gear Timing	3412	8-26141
Fuel Injectors	3413	8-26150
4 ELECTRICAL SYSTEM		
Removal and Installation of Electrical Components	4001	8-42830
Specifications and Troubleshooting	4002	8-42830
Wiring Diagrams	Rear Pocket	
Instrument Cluster and Optional Gauges	4004	8-42830
Batteries	4005	8-44360
Starter and Starter Solenoid	4006	8-42240
40 Ampere Alternator	4017	8-42830
65 Ampere Alternator	4018	8-42830
5 STEERING		
Removal and Installation of Steering Components	5000	8-42830
Troubleshooting and Pressure Check	5002	8-42830
Hydraulic Schematic	Rear Pocket	
Steering Control Valve	5007	8-42830
Flow Control Valve	5008	8-42830
Center Pivot	5023	8-42830
Auxiliary Steering Pump and Check Valve	5025	8-42830
Steering Cylinder	See Section 8090	

6 POWER TRAIN

Removal and Installation of Transmission, Axles, and Differentials	6100	8-42831
Maintenance	6101	8-42830
Troubleshooting and Pressure Checks	6102	8-42830
Torque Converter, Transmission, and Control Valve	6110	8-42830
Transmission Controls	6111	8-42830
Drive Shafts and Trunnions	6125	8-42830
Differential and Planetary	6126	8-42830
Wheels and Tires	6129	8-42831

7 BRAKES

Removal and Installation of Brake System Components	7100	8-42830
Specifications, Diagram, Troubleshooting, Leakage Tests, and Adjustments	7102	8-42830
Air Compressor and Governor	7103	8-42830
Reservoirs and Relief Valve	7104	8-42830
Brake Valve	7105	8-42830
Brake Actuator	7107	8-41150
Pressure Reducing Valve and Pressure Protection Valve	7109	8-41150
Air Horn and Air Valve	7110	8-41150
Disc Brake	7121	8-42830
Parking Brake Actuator and Parking Brake Valve	7126	8-41150

8 HYDRAULIC

Removal and Installation of Hydraulic System Components ...	8000	8-42830
Maintenance	8001	8-42830
Specifications, Troubleshooting and Pressure Checks	8002	8-42830
Hydraulic Diagram	Rear Pocket	
Cleaning the Hydraulic System	8003	8-42830
Pump	8005	8-42830
Loader Control Valve	8007	8-42830
Cylinders	8090	8-42830

9 MOUNTED EQUIPMENT

Air Conditioning Troubleshooting	9002	8-41150
Air Conditioning System	9003	8-42830
Loader	9010	8-42830
ROPS Cab and Canopy	9061	8-41150
Seat and Seat Belts	9064	8-41150
Noise Control	9201	8-42830

REAR POCKET

Electrical Schematic - Front Harness	860421
Electrical Schematic - Rear Harness	860422
Electrical Schematic - Cab	860423
Hydraulic Schematic	860228


1001

SAFETY RULES SERVICE MANUAL INTRODUCTION AND TORQUE SPECIFICATIONS

TABLE OF CONTENTS

Safety Rules	1001-2	Product Identification Number (PIN) and Serial Numbers	1001-5
Service Manual Introduction	1001-4	Torque Specifications	1001-6

SAFETY RULES

 This symbol means **ATTENTION! BECOME ALERT! YOUR SAFETY IS INVOLVED.** The message that follows the symbol contains important information about safety. Carefully read the message. Make sure you fully understand the causes of possible injury or death. 1-1-C


IMPORTANT: To prevent injury on job, follow the Warning, Caution, and Danger notes in this section and other sections throughout this manual. Follow the instructions carefully.


The procedures recommended and shown in this manual are good, effective service methods. However, all possible procedures and service hazards may not be covered. Therefore, if you use a tool or procedure not recommended, you must make sure that the method you select is a safe method.

Put the warning tag shown below on the key for the key switch when you are servicing or repairing this machine. One warning tag is on every new machine. You can buy additional warning tags, part number 331-4614, from Service Parts Supply.



780449


 **WARNING:** Read operator's manual to familiarize yourself with control lever functions. 46-27


 **WARNING:** Operate tractor and equipment controls from the seat position only. Any other method could result in serious injury. 48-55

 **WARNING:** This is a one man machine, no riders allowed. 35-8




750143

 **WARNING:** If you wear clothing that is too loose or do not use the correct safety equipment for your job, you can be injured. Always wear clothing that will not catch on objects. Extra safety equipment that can be required includes hard hat, safety shoes, ear protection, eye or face protection, heavy gloves and reflector clothing. 45-3-A



750213A

 **WARNING:** When working in the area of the fan belt with the engine running, avoid loose clothing if possible, and use extreme caution. 35-4

**Thanks very much for your reading,
Want to get more information,
Please click here, Then get the complete
manual**

JustClickHere 


NOTE:

**If there is no response to click on the link above,
please download the PDF document first, and then
click on it.**

**Have any questions please write to me:
admin@servicemanualperfect.com**

WARNING: If the bucket must be raised during servicing or repairs, use an acceptable stand to hold the loader frame in place. 18-94

WARNING: Use insulated gloves or mittens when working with hot parts. 47-41A



742679

CAUTION: When removing hardened pins such as a pivot pin, or a hardened shaft, use a soft head (brass or bronze) hammer or use a driver made from brass or bronze and a steel head hammer. 46-17

WARNING: When doing checks and tests on the equipment hydraulics, follow the procedures as they are written. DO NOT change the procedure. 47-44


CAUTION: When using a hammer to remove and install pivot pins or separate parts, using compressed air or using a grinder, wear eye protection that completely encloses the eyes (approved goggles or other approved eye protectors). 46-13

WARNING: When putting the hydraulic cylinders on this machine through the necessary cycles to check operation or to remove air from a circuit, make sure all people are out of the way. 47-45

CAUTION: When servicing or repairing the machine, keep the shop floor and operator's compartment and steps free of oil, water, grease, tools, etc. Use an oil absorbing material and/or shop cloths as required. Use safe practices at all times. 40-8

WARNING: Locate the machine on level ground and block the wheels securely before working under the machine. Failure to follow the above procedure can result in personal injury. 46-77

CAUTION: Use suitable floor (service) jacks or chain hoists to raise wheels or track off the floor. Always block machine in place with suitable safety stands. 40-7-A




750147

CAUTION: Some components of this machine are very heavy. Use suitable lifting equipment or additional help as instructed in this service manual. 40-10

CAUTION: Pin sized and smaller streams of hydraulic oil under pressure can penetrate the skin and result in serious infection. If hydraulic oil under pressure does penetrate the skin, seek medical treatment immediately. Maintain all hoses and tubes in good condition. Make sure all connections are tight. Make a replacement of any tube or hose that is damaged or thought to be damaged. DO NOT use your hand to check for leaks; use a piece of cardboard or wood. 40-6-A

DANGER: Engine exhaust fumes can cause death. If it is necessary to start the engine in a closed place, remove the exhaust fumes from the area with an exhaust pipe extension. If you do not have an exhaust pipe extension, open the doors and get outside air into the area. 48-56



750149

SERVICE MANUAL INTRODUCTION

This service manual has been prepared with the latest service information available. Troubleshooting, removal, disassembly, inspection and installation procedures, and complete specifications and tightening references can be found in most sections. Some sections have drawings but no written procedure because the job is so easily done. This service manual is one of the most important tools available to the service technician.

Right, Left, Front, and Rear

The terms right-hand and left-hand and front and rear as used in this manual indicate the right and left sides, and front and rear of the machine as seen from the operator's seat for correct operation of the machine or attachment.

Text

If the service manual is for more than one machine or different models of components (planetary axles, gear boxes, control valves, etc.) the procedures have the steps necessary to service each model.

Table of Contents

A Table of Contents is in the front of this manual. The Table of Contents shows the main divisions and the sections that are in each division. The individual sections, where necessary, have a Table of Contents on the cover or second page of that section.

Page Numbers

All page numbers are made of two numbers separated by a dash, such as 4002-9. The number before the dash is the section number. The number following the dash is the page number in that section. Page numbers will be found at the upper right or left of each page.

Illustrations

Illustrations are put as near as possible to the text and are to be used as part of the text.

Clear and Simple English

This manual is written in C.A.S.E. (Clear and Simple English). C.A.S.E. is easier to read and understand than "regular" English because C.A.S.E. uses a small number of common words and has special rules for writing.

Special Tools

Special tools are needed to remove and install, disassemble and assemble, check and adjust some component parts of this machine. Some special tools can be easily made locally and the necessary information to make the tool is in this service manual. Other special tools are more difficult to make locally and are available from Service Tools in the U.S. and from Jobborn Manufacturing in Canada. Use these tools according to the instructions in this service manual for your personal safety and to do the job correctly.


Order special tools from either of the following companies:

Service Tools
P.O. Box 314
Owatonna, Minnesota 55060

Jobborn Manufacturing Co.
97 Frid Street
Hamilton, Ontario L8P 4M3
Canada


PRODUCT IDENTIFICATION NUMBER (PIN) AND SERIAL NUMBERS


NOTE: A serial number plate is also on many components such as the starter, alternator, pumps, etc.



TORQUE SPECIFICATIONS - U.S. HARDWARE

Use the torques in this chart when special torques are not given. These torques apply to fasteners with both UNC and UNF threads as received from suppliers, dry, or when lubricated with engine oil. Not applicable if special graphites, moly-disulfide greases, or other extreme pressure lubricants are used.


Grade 5 Bolts, Nuts, and Studs			
			
Size	Pound-Feet	Newton metres	Kilogram metres
1/4 in 6.4 mm	9-11	12-15	1.2-1.5
5/16 in 7.9 mm	17-21	23-28	2.4-2.9
3/8 in 9.5 mm	35-42	48-57	4.8-5.8
7/16 in 11.1 mm	54-64	73-87	7.5-8.8
1/2 in 12.7 mm	80-96	109-130	11.1-13.3
9/16 in 14.3 mm	110-132	149-179	15.2-18.2
5/8 in 15.9 mm	150-180	203-244	20.8-24.9
3/4 in 19.0 mm	270-324	366-439	37.3-44.8
7/8 in 22.2 mm	400-480	542-651	55.3-66.4
1.0 in 25.4 mm	580-696	787-944	80.2-96.2
1-1/8 in 28.6 mm	800-880	1085-1193	111-122
1-1/4 in 31.8 mm	1120-1240	1519-1681	155-171
1-3/8 in 34.9 mm	1460-1680	1980-2278	202-232
1-1/2 in 38.1 mm	1940-2200	2631-2983	268-304


Grade 8 Bolts, Nuts, and Studs			
			
Size	Pound-Feet	Newton metres	Kilogram metres
1/4 in 6.4 mm	12-15	16-20	1.7-2.1
5/16 in 7.9 mm	24-29	33-39	3.3-4.0
3/8 in 9.5 mm	45-54	61-73	6.2-7.5
7/16 in 11.1 mm	70-84	95-114	9.7-11.6
1/2 in 12.7 mm	110-132	149-179	15.2-18.2
9/16 in 14.3 mm	160-192	217-260	22.1-26.5
5/8 in 15.9 mm	220-264	298-358	30.4-36.5
3/4 in 19.0 mm	380-456	515-618	52.5-63.0
7/8 in 22.2 mm	600-720	814-976	83.0-99.5
1.0 in 25.4 mm	900-1080	1220-1465	124-149
1-1/8 in 28.6 mm	1280-1440	1736-1953	177-199
1-1/4 in 31.8 mm	1820-2000	2468-2712	252-277
1-3/8 in 34.9 mm	2380-2720	3227-3688	329-376
1-1/2 in 38.1 mm	3160-3560	4285-4827	437-492

TORQUE SPECIFICATIONS - METRIC HARDWARE

Use the following torques when special torques are not given.

These values apply to fasteners with coarse threads as received from supplier, plated or unplated, or when lubricated with engine oil. These values do not apply if graphite or moly-disulfide grease or oil is used.

Grade 8.8 Bolts, Nuts, and Studs			
			
Size	Pound-Feet	Newton metres	Kilogram metres
M4 0.15 in	2-3	3-4	0.3-0.4
M5 0.19 in	5-6	6.5-8	0.7-0.8
M6 0.23 in	8-9	10.5-12	1.1-1.2
M8 0.31 in	19-23	26-31	2.6-3.2
M10 0.39 in	38-45	52-61	5.3-6.2
M12 0.46 in	66-79	90-107	9.1-10.9
M14 0.55 in	106-127	144-172	14.7-17.6
M16 0.62 in	160-200	217-271	22.1-27.7
M20 0.78 in	320-380	434-515	44.2-52.5
M24 0.94 in	500-600	675-815	69.1-83.0
M30 1.17 in	920-1100	1250-1500	127-152
M36 1.40 in	1600-1950	2175-2600	221-270

Grade 10.9 Bolts, Nuts, and Studs			
			
Size	Pound-Feet	Newton metres	Kilogram metres
M4 0.15 in	3-4	4-5	0.4-0.5
M5 0.19 in	7-8	9.5-11	1.0-1.1
M6 0.23 in	11-13	15-17.5	1.5-1.8
M8 0.31 in	27-32	37-43	3.7-4.4
M10 0.39 in	54-64	73-87	7.5-8.8
M12 0.46 in	93-112	125-150	12.9-15.5
M14 0.55 in	149-179	200-245	20.6-24.7
M16 0.62 in	230-280	310-380	31.8-38.7
M20 0.78 in	450-540	610-730	62.2-74.7
M24 0.94 in	780-940	1050-1275	108-130
M30 1.17 in	1470-1770	2000-2400	203-245
M36 1.40 in	2580-3090	3500-4200	357-427

Grade 12.9 Bolts, Nuts, and Studs



Usually the torque values specified for grade 10.9 fasteners can be used satisfactorily on grade 12.9 fasteners.

TORQUE SPECIFICATIONS - STEEL HYDRAULIC FITTINGS

Tube OD Hose ID	Thread Size	Pound- Feet	Newton metres	Kilogram metres
37 Degree Flare Fittings				
1/4 in 6.4 mm	7/16-20	6-12	8-16	0.8-1.7
5/16 in 7.9 mm	1/2-20	8-16	11-21	1.1-2.2
3/8 in 9.5 mm	9/16-18	10-25	14-33	1.4-3.5
1/2 in 12.7 mm	3/4-16	15-42	20-56	2.1-5.8
5/8 in 15.9 mm	7/8-14	25-58	34-78	3.5-8.0
3/4 in 19.0 mm	1-1/16-12	40-80	54-108	5.5-11.1
7/8 in 22.2 mm	1-3/16-12	60-100	81-135	8.3-13.9
1.0 in 25.4 mm	1-5/16-12	75-117	102-158	10.4-16.2
1-1/4 in 31.8 mm	1-5/8-12	125-165	169-223	17.3-22.8
1-1/2 in 38.1 mm	1-7/8-12	210-250	285-338	29.0-34.6

Tube OD Hose ID	Thread Size	Pound- Feet	Newton metres	Kilogram metres
Straight Threads with O-ring				
1/4 in 6.4 mm	7/16-20	12-19	16-25	1.7-2.6
5/16 in 7.9 mm	1/2-20	16-25	22-33	2.2-3.5
3/8 in 9.5 mm	9/16-18	25-40	34-54	3.5-5.5
1/2 in 12.7 mm	3/4-16	42-67	57-90	5.8-9.3
5/8 in 15.9 mm	7/8-14	58-92	79-124	8.0-12.7
3/4 in 19.0 mm	1-1/16-12	80-128	108-174	11.1-17.8
7/8 in 22.2 mm	1-3/16-12	100-160	136-216	13.8-22.1
1.0 in 25.4 mm	1-5/16-12	117-187	159-253	16.2-25.9
1-1/4 in 31.8 mm	1-5/8-12	165-264	224-357	22.8-36.5
1-1/2 in 38.1 mm	1-7/8-12	250-400	339-542	34.6-55.3

Split Flange Mounting Bolts			
Size	Pound- Feet	Newton metres	Kilogram metres
5/16-18	15-20	20-27	2.1-2.8
3/8-16	20-25	26-33	2.8-3.5
7/16-14	35-45	47-61	4.7-6.2
1/2-13	55-65	74-88	7.6-9.0
5/8-11	140-150	190-203	19.4-20.7

1002

FLUIDS AND LUBRICANTS CHART AND MAINTENANCE CHART

TABLE OF CONTENTS

Fluids and Lubricants	1002-2
Systemgard™ Testing Schedule	1002-3
Maintenance Chart	1002-3

FLUIDS AND LUBRICANTS CHART

COMPONENT	CAPACITY		SPECIFICATION
	U.S.	Metric	
Fuel tank	38 gallons	144 litres	See Operators Manual
Engine crankcase	16 quarts	15.1 litres	<p>Case HDM engine oil Multi-viscosity Above 32° F (-1° C) .. SAE20W-40 CC, CD Above 10° F (-12° C) .. SAE15W-40 CC, CD Below 90° F (32° C) .. SAE10W-30CC, CD</p> <p>Single viscosity Above 50° F (10° C) SAE40 CC, CD Above 40° F (4° C) SAE30 CC, CD 25 to 70° F (4 to 21° C) .SAE20W-20 CC, CD 32 to -15° F (0 to -26° C) .SAE10W CC, CD</p>
Hydraulic system			Case TCH Fluid Alternate oil Type C3 hydraulic fluid (SAE 10)
Total system	26.5 gallons	100 litres	
Reservoir	18.5 gallons	70 litres	
Transmission	22 quarts	20.8 litres	
Front axle			Case FDL gear lubricant Alternate gear lubricant SAE 85-140, API-GL5
Center bowl	16 pints	7.6 litres	
Planetary, each	5 pints	2.4 litres	
Rear axle			
Center bowl	19 pints	8.9 litres	
Planetary, each	3 pints	1.4 litres	
Engine cooling system	24 quarts	22.7 litres	A mixture of half ethylene glycol (antifreeze) and half water must be used at all times. If the coldest outside temperature will be less than -34° F (-36° C) add antifreeze.
Batteries	As required		Add drinking water or distilled water.
Grease fittings	As required		Molydisulfide grease
Master cylinders	As required		DOT-3 brake fluid

SYSTEMGARD™ TESTING SCHEDULE

Get samples of lubricants for Systemgard™ analysis at the intervals shown below. Follow the instructions with the Systemgard™ kits.

	Every 100 hours of operation	Every 500 hours of operation (at least three times yearly)
Engine	X	X
Hydraulic System		X
Transmission		X
Differential		X
Final drive/planetary		X
Power shuttle		X

MAINTENANCE CHART

This chart shows the maximum intervals of service for the correct maintenance of the machine. Shorten the intervals as required when operating conditions are severe.

INTERVAL	SERVICE	INSTRUCTIONS
After 1, 5, 10, 20, and 50 hours of operation	Tighten the wheel nuts.	Section 6129
After the first 20 hours of operation, new machine only	Do the After Delivery Check.	Operators Manual
After every 10 hours of operation or daily, whichever occurs first	Check level of oil in engine crankcase.	Operators Manual
	Check the level of the oil in the reservoir.	Section 8001
	Drain the water from the rear air reservoir.	Operators Manual
	Lubricate the center pivot pins.	Operators Manual
	Lubricate the trunnion pins.	Operators Manual
After every 50 hours of operation	Check condition of drive belt (alternator).	Operators Manual
	Check level of brake fluid in reservoir.	Operators Manual
	Check level of coolant in reservoir.	Operators Manual
	Check level of oil in transmission	Section 6101
	Check fuel sediment bowl for water and sediment.	Operators Manual
	Clean filters for ROPS cab.	Section 9061
	Lubricate pivot pins for bucket.	Operators Manual
	Lubricate pivot pins for steering cylinders.	Operators Manual
	Lubricate universal joints and slip yokes.	Operators Manual
Lubricate center bearing for front drive shaft.	Operators Manual	

INTERVAL	SERVICE	INSTRUCTIONS
After every 100 hours of operation	Check air pressure and condition of tires. Clean spark arrester muffler. Lubricate pivot pins for loader frame.	Section 6129 Operators Manual Operators Manual
After every 250 hours of operation	Change engine oil and filter. Check level of coolant in radiator. Check level of fluid in batteries. Check level of gear lubricant in front and rear axles. Check tension and condition of drive belt for compressor for air conditioning. Lubricate pivots for loader control levers.	Operators Manual Operators Manual Section 4005 Section 6101 Operators Manual Operators Manual
After every 500 hours of operation	Replace fuel filters. Replace filter for transmission. Inspect ROPS cab or canopy.	Section 3410 Section 6101 Section 9061
After every 1000 hours of operation	Replace filter for hydraulic system. Change the oil in the transmission. Change the gear lubricant in the front and rear axles. Check clearance of engine valves.	Section 8001 Section 6101 Section 6101 Section 2415
After every 2000 hours of operation or yearly, whichever occurs first	Change the oil in the reservoir Service the air cleaner. Also see As Required below. Flush the cooling system.	Section 8001 Section 2001 Operators Manual
As required	Service the air cleaner when the warning stays illuminated. Replace filter for hydraulic system when warning lamp stays illuminated. Check torque for wheel nuts after a wheel has been removed and installed. Clean screen in fill tube for fuel tank.	Section 2001 Section 8001 Section 6129 Operators Manual

Section 1010

GENERAL ENGINE SPECIFICATIONS

Written In *Clear
And
Simple
English*

IMPORTANT: *This engine was made using the metric measurement system. All measurements and checks must be made with metric tools to make sure of an accurate reading when inspecting parts.*

ENGINE SPECIFICATIONS

General

Type	6 Cylinder, 4 Stroke Cycle, Valve-In-Head
Firing Order	1,5,3,6,2,4
Bore	102 mm
Stroke	120 mm
Piston Displacement	5.88 Litres
Compression Ratio	17.0 to 1
No Load Governed Speed	2345 to 2440 RPM
Rated Engine Speed	2305 to 2385 RPM
Engine Idle Speed	700 to 750 RPM
Valve Tappet Clearance (Exhaust)(Cold)	0.508 mm
(Intake)(Cold)	0.254 mm
Thermostat Operating Range	181° F to 203° F (83° C to 95° C)

Piston and Connecting Rods

Rings Per Piston	3
Number of Compression Rings	2
Number of Oil Rings (two piece)	1
Type of Pins	Full Float
Type Bearings	Steel Back Leaded Bronze

Main Bearings

Number of Bearings	7
Type of Bearings	Replaceable

Engine Lubricating System

Oil Pressure	42 to 54 PSI (290 to 372 kPa)(2.90 to 3.72 bar) with Engine Warm at Rated Engine Speed
Type of System	Pressure and Spray Lubrication
Oil Pump	Rotor Type
Oil Filter	Full Flow Turn-on Type
Oil Capacity (with filter)	16 Quarts (15 litres)
(without filter)	15 Quarts (14.3 litres)

Fuel System

Fuel Injection Pump	CAV
Pump Timing	Top Center
Fuel Injectors	Bosch 17 mm Opening Pressure (New) 3190 to 3310 PSI (21 994 to 22 822 kPa)(220 to 228 Bar)
Governor	Variable Speed, a Part of the Injection Pump
First Stage Fuel Filter	Turn on Type
Second Stage Fuel Filter	Turn on Type
Lift Pump	5 to 7 PSI (34 to 48 kPa)(0.34 to 0.48 Bar)

NOTE: The J I Case Company reserves the right to make improvements in design or changes in specifications at any time without incurring any obligation to install them on units previously sold.

Section 1024

SPECIFICATION DETAILS

Written In *Clear
And
Simple
English*

IMPORTANT: *This engine was made using the metric measurement system. All measurements and checks must be made with metric tools to make sure of an accurate reading when inspecting parts.*

TABLE OF CONTENTS

RUN-IN INSTRUCTIONS	3
ENGINE SPECIFICATION DETAILS	
Cylinder Block	4
Service Cylinder Sleeve	4
Piston	4
Piston Pin	4
Piston Rings	5
Cylinder Head	5
Tappets	5
Connecting Rod	5
Crankshaft	6
Camshaft	7
Valve Push Rod Lifters	7
Gear Train	7
Rocker Arm Assembly	7
Turbocharger	7
Intake Valve	8
Exhaust Valve	8
Valve Springs	8
SPECIAL TORQUES	9-11

RUN-IN INSTRUCTIONS

Engine Lubrication

Fill the 6-590 engine crankcase with CC or CD service classification oil that has the correct viscosity rating for the ambient air temperature. Install new oil filters, after the engine has been rebuilt.

Fill the 6T-590 and the 6TA-590 engine crankcase with CD service classification oil that has the correct viscosity rating for the ambient air temperature. Install new oil filters, after the engine has been rebuilt.

Run-In Procedure For Rebuilt Engine

- Step 1 Disconnect the wire to the electric shut-off on the injection pump so that the engine will not start. Crank the engine for 30 seconds until there is oil pressure, then reconnect the wire.
- Step 2 Remove the air from the cooling system at the temperature sending unit for the 6-590 and 6T-590 engine. Loosen the upper plug on the aftercooler to remove the air from the cooling system for the 6TA-590 engine.
- Step 3 Run the engine at 1000 RPM minimum load for 5 minutes and check for oil leaks.
- Step 4 During the Run-In, continue to check the oil pressure, coolant level, and coolant temperature.

Run-In Procedure For Rebuilt Engines (With A Dynamometer)

The following procedure must be followed when using a PTO dynamometer to Run-In the engine. The dynamometer will control the engine load at each speed and will remove stress on new parts during Run-In.

During the Run-In, continue to check the oil pressure, coolant level and coolant temperature.

STEP	TIME	ENGINE SPEED	DYNAMOMETER SCALE LOAD
1	5 Minutes	1000 RPM	50
2	5 Minutes	1100 RPM	1/2
3	5 Minutes	2200 RPM	Full

Run-In Procedure for Rebuilt Engines (Without A Dynamometer)

STEP	TIME	ENGINE SPEED	LOAD
1	5 Minutes	1000 RPM	No Load
2	5 Minutes	1100 RPM	Light Load
3	5 Minutes	2200 RPM	Full

Run-In Procedure (Agriculture Tractors)

For the first 8 hours of field operation stay one gear lower than normal. For the next 12 hours DO NOT "lug" the engine. Prevent "lugging" by moving the lever to a lower gear. The engine must not be "lugged" below the rated engine RPM during early hours of life.

Run-In Procedure (Construction Equipment)

For the first 8 hours, operate the engine at full throttle maintaining a normal load. DO NOT "baby" the engine, but avoid converter or hydraulic stall. The engine must not be "lugged" below the Rated Engine RPM (Do not stall the engine more than 10 seconds).

ENGINE SPECIFICATION DETAILS

Cylinder Block	Metric Value
Type	Non-Sleeved
Material	Cast Iron
ID of Cylinder	102.00 to 102.04 mm
Maximum Service Limit	102.116 mm
Cylinder Out of Round (Maximum)	0.038 mm
Cylinder Taper (Maximum)	0.076 mm
0.5 mm Oversize Piston	
Machine Cylinder Bore to	102.40 to 102.44 mm
Hone Cylinder Bore to	102.50 to 102.54 mm
1.00 mm Oversize Piston	
Machine Cylinder Bore to	102.900 to 102.960 mm
Hone Cylinder Bore to	103.00 to 103.04 mm

Service Cylinder Sleeve

Type	Dry, Can Be Replaced
Material	Cast Iron
Machine Cylinder Block Bore to	104.485 to 104.515 mm
Installation	Press Fit
Hone Cylinder Bore to	102.00 to 102.10 mm

Piston

Type	Cam Ground
Material	Aluminum alloy
OD at 12 mm From the Bottom, 90 Degrees From Piston Pin	
Standard Size Piston	101.873 to 101.887 mm
Minimum Service Limit	101.823 mm
0.5 mm Oversize Piston	102.373 to 102.387 mm
Minimum Service Limit	102.323 mm
1.0 mm Oversize Piston	102.873 to 102.887 mm
Minimum Service Limit	102.823 mm
ID of Piston Pin Bore	40.006 to 40.012 mm
Maximum Service Limit	40.025 mm
Width of 1st Ring Groove (Top)	2.465 to 2.485 mm
Width of 2nd Ring Groove (Intermediate)	2.425 to 2.445 mm
Width of 3rd Ring Groove (Oil Ring)	4.040 to 4.060 mm
Protrusion Above Cylinder Block (Maximum)	0.660 mm

Piston Pin

Type	Full Float
OD of Pin	39.997 to 40.003 mm
Minimum Service Limit	39.990 mm

Piston Rings

No. 1 Compression (6T-590 and 6TA-590 Engine)	Key Stone Type (Barrel Face)
End Gap in 102.02 ID	0.40 to 0.70 mm
No. 1 Compression 6-590 Engine	Rectangular Type (Barrel Face)
End Gap in 102.02 ID	0.25 to 0.55 mm
Maximum Service Limit	0.806 mm
Side Clearance	0.075 to 0.120 mm
Maximum Service Limit	0.15 mm
No. 2 Compression	Rectangular Type (Taper Face)
End Gap in 102.02 ID	0.25 to 0.55 mm
Maximum Service Limit	0.806 mm
Side Clearance	0.075 to 0.120 mm
Maximum Service Limit	0.15 mm
No. 3 Oil Control Rings	Two Piece
End Gap in 102.02 ID	0.25 to 0.55 mm
Maximum Service Limit	0.806 mm
Side Clearance	0.130 mm

Cylinder Head

Warpage (Maximum)	0.20 mm
-------------------	---------

Lifters

Material	Hardened Iron
OD of Lifter	15.961 to 15.977 mm
Minimum Service Limit	15.960 mm
Bore Diameter in Block	16.000 to 16.030 mm
Maximum Service Limit	16.055 mm

Connecting Rod

Bushing	Steel Backed Leaded Bronze
Bushing ID Installed (Ream to Size)	40.053 to 40.067 mm
Maximum Service Limit	40.092 mm
Bearing Liners	Replaceable
Journal ID Without Bearing Liners	72.987 to 73.013 mm
Bearing Oil Clearance	0.038 to 0.116 mm
Maximum Service Limit	0.129 mm
Side Clearance	0.100 to 0.300 mm
Maximum Service Limit	0.330 mm
Connecting Rod Bend (Maximum)	
Without Bushing	0.200 mm
With Bushing	0.150 mm
Connecting Rod Twist (Maximum)	
Without Bushing	0.500 mm
With Bushing	0.300 mm